


MALONE

CHANGING THE WAY YOU GET THERE



Installation & Loading Instructions - Please Read Before Beginning



Step 1: Installing Carriers to Cross Bars

- Insert a Mounting Bolt into one of the top side hex holes. See image 1.

- Insert Mounting Bolt through one hole of a Jawz Mounting Adapter and loosely apply a T-knob. See image 2.



- Place the carrier onto the front cross bar. Swing the Jawz under the cross bar as shown. See image 3.

MALONE®

CHANGING THE WAY YOU GET THERE

Installation & Loading Instructions - MPG107M (MD) SeaWing™



- 4. Insert a second Mounting Bolt into the top side unused carrier hex hole and down through the Jawz mounting adapter. Apply a second T-knob and slightly tighten until the carrier is secure. Repeat steps 1-4 for the 2nd carrier and rear cross bar. See image 4.

- 5. Confirm the carriers are in alignment. Firmly tighten the T-knobs until both carriers are securely fixed to the cross bars. See image 5.



- 6. Insert the four Rubber Plugs into the four top side hex holes in the two carriers. See image 6.

Step 2: Loading the Kayak

- 7. Route the free end of a 12' Load Strap down through the top of the outer most strap slot and back up through the inside slot of the carrier. Pull the free end until there is an even loop. Repeat for the second carrier. See image 7.



MALONE[®]

CHANGING THE WAY YOU GET THERE

Installation & Loading Instructions - MPG107M (MD) SeaWing™



- Place the straps parallel to the carriers with the front strap loop on the windshield and the rear strap loop on the back of the vehicle. See image 8.

- Place a mat on the rear of the vehicle to protect the finish. Lift the front of the kayak onto the vehicle. Lift the rear of the kayak up and slide it into the carriers. See image 9.



- Position kayak so that the cockpit is evenly centered between the front and rear carriers. The bottom of the kayak should be slightly elevated above each of the carriers and held by the sides of the carriers. See image 10.

- Place the strap loops over the kayak so that each loop is positioned directly over a carrier. See image 11.



MALONE[®]

CHANGING THE WAY YOU GET THERE

Installation & Loading Instructions - MPG107M (MD) SeaWing™



- . Pull the free end of each strap loop down until the buckles are positioned half way up the side of the kayak. Thread each free end down and through the top of the outside slot and back up through the bottom of the inside slot. See image 12.

- . Thread the free strap ends up and through the buckles. Pull down to tighten. Dress any extra strap down and around the cross bars. See image 13.



- . For MD series: Install the bow & stern safety lines per the attached instructions.

IMPORTANT NOTES:

For added stability for larger kayaks, dress the straps down under the cross bars before bringing them back up through the slots in steps 7 and 12.

Safety tie-downs are required for all transport. If your kit did not include safety tie-downs, we strongly recommend the use of the Malone MPG316 Sentry Ratchet Tie-Down System.

Always check mounting hardware, load straps and safety tie-down lines for proper and secure attachment before transport. Use of this product for any other application other than kayak transport voids warranty.

MALONE

CHANGING THE WAY YOU GET THERE


MPG370 BOW & STERN LINE KIT



Attach hook to rope (steps A-D)



Thread free end of cord through hook.



Create a "left over right" knot & tighten.



Create a "right over left" knot & tighten.



Pull to test for knot strength.


Attach and dress rope to vehicle and boat (steps E-O)




Attach S-hook to vehicle tow ring or other sturdy body part.



Keeping the rope tight and S-hook in place, thread the free end up and through a strong point on the kayak



Make a loop in the rope 12" to 14" away from the kayak or canoe.



Bend the loop over leaving a large opening as shown.



Pass the loop through the opening.



Pull to create a tight knot.



Thread the free end of the rope through the loop.



Pull the free end up until the rope is sufficiently tight.



Hold the rope secure with one hand.



Form a knot with the free end and tighten. Form a second knot for safety purposes.



The line should be tight and secure. Repeat for second tie-down.

MALONE[®]

CHANGING THE WAY YOU GET THERE

Limited Lifetime Warranty

The Malone Auto Racks (Malone) Limited Lifetime Warranty covers certain Malone-brand products that have been specifically identified for inclusion in the program and is effective for as long as the original retail purchaser owns the product. This warranty is terminated when the original retail purchaser sells or otherwise transfers the product to any other person or entity.

Subject to the limitations and exclusions described in this warranty, Malone will remedy defects in materials and/or workmanship by repairing or replacing, at its option, a defective product without charge for parts or labor. Malone may elect, at its option, not to repair or replace a defective product but rather issue to the original retail purchaser a refund equal to the purchase price paid for the product, or credit to be used toward the purchase of a replacement Malone product.

This warranty does not cover, and no warranty is given for defects or problems caused by normal wear and tear which includes but is not limited to surface (aesthetic) metal corrosion, scratches, dents, deformities, accidents, unlawful vehicle operation, or any modification of a product not performed or authorized in writing by Malone.

In addition, this warranty does not cover problems resulting from conditions beyond Malone's control including, but not limited to, theft, misuse, overloading, or failure to assemble, mount or use the product in accordance with Malone's written instructions or guidelines included with the product available to the original retail purchaser.

No warranty is given for any Malone products purchased outside of the United States, Canada, Mexico, Australia and New Zealand.

If the product is believed to be defective, the original retail purchaser should contact the Malone dealer from whom it was purchased, who will give the original retail purchaser instructions on how to proceed. If the original retail purchaser is unable to contact the Malone dealer, or the dealer is not able to remedy the defect, the original retail purchaser should contact Malone by email at technical@maloneautoracks.com.

In the event that the product must be returned to Malone, a technician at the email address above will provide the original purchaser with return shipping instructions. The original purchaser will be responsible for the cost of mailing the product to Malone. In order to receive any remedy under this warranty, a copy of the original purchase receipt, a description of the defect and a return address must be provided.

Disclaimer of Liability

Repair or replacement of a defective product, or the issue of a refund or credit (as determined by Malone) is the original retail purchaser's exclusive remedy under this warranty. Damage to original purchaser's vehicle, cargo, or property, and/or to any other person or property is not covered by this warranty.

This warranty is expressly made in lieu of any and all other warranties, express or implied, including the warranties of merchantability and fitness for a particular purpose.

Malone's sole liability is limited to the remedy set forth above. In no event will Malone be liable for any direct, indirect, consequential, incidental, special, exemplary, or punitive damages, or, for any other damages of any kind or nature (including but not limited to, lost profits, lost income or lost sales).

Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitations may not be applicable. This warranty gives you specific legal rights and you may also have other rights which vary from state to state.

In addition, all vehicular transports are potentially hazardous. Any person using MALONE products are personally responsible for following the given directions for use, installation and accepts full responsibility for any and all damages or injury of any kind including death, which may result from their use.



Exonération de responsabilité

La réparation ou le remplacement d'un produit défectueux, ou l'émission d'un remboursement ou d'un crédit, tel que déterminé par Malone, constitue la seule réclamation offerte à l'acheteur original du produit selon les termes de cette garantie. Les dommages causés au véhicule de l'acheteur original, à son chargement, à ses biens et/ou à toute autre personne ou autres biens ne sont pas couverts par la présente garantie.

La présente garantie est formulée uniquement et expressément en remplacement de toute autre garantie, explicite ou tacite, y compris les garanties de qualité marchande et d'aptitude à une fin donnée.

L'unique responsabilité endossée par Malone se limite aux réclamations énoncées ci-dessus. Malone ne sera responsable, en aucun cas, des dommages directs, indirects, consécutifs, spéciaux, exemplaires ou punitifs, ou de tout autre dommage, quel qu'en soit la cause, incluant, mais ne se limitant pas, à la perte de profits, de revenus ou de ventes.

Certains états ne permettent pas l'exclusion des dommages consécutifs ou indirects. Certaines des restrictions énoncées ci-dessus pourraient, de ce fait, ne pas s'appliquer. La présente vous procure certaines garanties juridiques spécifiques. Vous pourriez également bénéficier d'autres garanties, celles-ci pouvant varier d'un état à l'autre.

En outre, le transport en véhicule, de quelque nature qu'il soit, comporte des risques potentiels. Toute personne utilisant un produit MALONE a la responsabilité de suivre adéquatement les instructions fournies ainsi que les directives d'assemblage et accepte l'entière responsabilité quant aux dommages ou blessures en tout genre, incluant le décès, pouvant résulter de son utilisation.

MALONE

CHANGING THE WAY YOU GET THERE®

Garantie à vie limitée

La garantie à vie limitée offerte par Malone Auto Racks (Malone) couvre certains produits de marque Malone qui ont été spécifiquement inclus dans ce programme et est valide tant que l'acheteur original est propriétaire du produit. La présente garantie prend fin lorsque l'acheteur original vend ou cède ce produit à une tierce partie.

Sous réserve des restrictions et exclusions décrites aux termes de cette garantie, Malone corrigera toute défectuosité matérielle et/ou défaut de fabrication en réparant ou remplaçant sans frais, à sa discrétion, un produit défectueux incluant pièces ou main-d'œuvre. Malone pourrait décider, selon le cas, de ne pas réparer ou remplacer un produit défectueux mais plutôt de remettre à l'acheteur original du produit une somme égale au prix déboursé pour le produit ou offrir un crédit pouvant être utilisé à l'achat d'un produit de remplacement de Malone.

Cette garantie ne couvre pas les défectuosités ou les problèmes découlant d'une usure normale du produit et aucune garantie n'est offerte à cet effet. L'usure normale comprend, mais ne se limite pas à la corrosion métallique de surface (esthétique), aux égratignures, au bossellement, à la déformation, aux accidents, à l'utilisation illégale du produit ou à toute modification d'un produit n'ayant pas été effectuée par Malone ou pour laquelle aucune autorisation par écrit n'aura été obtenue au préalable.

En outre, cette garantie ne couvre pas les problèmes résultant de circonstances échappant au contrôle de Malone incluant, mais ne se limitant pas au vol, à une mauvaise utilisation du produit, à son surchargement, à un assemblage ou à un usage du produit ne respectant pas les instructions écrites ou directives du fabricant accompagnant le produit lors de son achat original.

Cette garantie ne s'applique pas aux produits Malone qui ont été achetés à l'extérieur des États-Unis, du Canada ou du Mexique.

Si le produit semble présenter une défectuosité, l'acheteur original du produit devrait contacter le détaillant auprès de qui l'achat a été effectué et celui-ci fournira à l'acheteur les informations concernant la marche à suivre. Si l'acheteur original se trouve dans l'impossibilité de contacter le dépositaire Malone, ou si ce dernier n'est pas en mesure de remédier à la défectuosité, l'acheteur original devrait contacter Malone, par courriel, à l'adresse suivante : technical@maloneautoracks.com.

Dans l'éventualité où le produit devait être retourné à Malone, des instructions concernant le retour de la marchandise seront fournies à l'acheteur original par un technicien qui aura été contacté par courriel, tel qu'indiqué ci-dessus. L'acheteur original devra défrayer les frais d'expédition. Pour être éligible à une réclamation selon les termes de cette garantie, l'acheteur original du produit doit fournir une copie du reçu original, une description de la défectuosité ainsi qu'une adresse de retour.